

Desk Microphone with Goose Neck

DESCRIPTION

- > Base station desk microphone with goose neck.
- > Attractive design.
- > High-sensitivity electret cartridge with amplifier.
- > PTT switch.
- > Special command board switching arrangements may be quoted upon request.
- > Voltage supply 9 - 15 V DC when connected as shown in the diagram below.
- > Supplied with 2 m cable.
- > Wind cap.



SPECIFICATIONS

Electrical	
Model	DM 6500 F/P
Type	Goose neck microphone
Pattern Type	Uni-directional
Impedance	Approx. 1 k Ω
Frequency Response	Shown in diagram below
Power Supply	Nominal : 2 V (Max. 10 V) directly on cartridge
Current Consumption	Approx. 0.5 mA
Sensitivity	-44 dB \pm 3 dB at 1 kHz rel. 1 V/Pa
Mechanical	
Cartridge Type	Electret
Materials	Brass and steel, epoxy lacquered. Impact-proof plastic
Cable	2 m 5-wire with shield
Dimensions	400 (typ.) x 108 x 145 mm / 15.75 (typ.) x 4.25 x 5.71 in.
Weight	Approx. 0.95 kg / 2.09 lb.
Environmental	
Operating temperature range	-25 °C to +55 °C
Storage Temperature Range	-40 °C to +55 °C

ORDERING

Model	Product No.
DM 6500 F/P	270000039

ADDITIONAL DATA

